



BARGE: GM 1014

ULLAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
1 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 PORT	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-1/2	- 01-1/2	02-0/8	- 02-0/8	02-1/2	- 02-1/2	03-1/8	- 03-1/8
3 STBD	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-1/2	- 01-1/2	02-0/8	- 02-0/8	02-1/2	- 02-1/2	03-1/8	- 03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS - 01-0/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11"

LENGTH BETWEEN DRAFT MARKS: 262'-00"

May 26, 2016

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK REFERENCE GAUGE HEIGHT: 16'-01 3/4"

Table with columns for IN, 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT. and rows for depth measurements from 0 to 11 feet.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 05/25/2016 BY: JM
DATE COMPUTED: 05/26/2016 BY: CL
DATE ISSUED: 05/26/2016



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-10 3/4"

IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.
0	0	0	4,137.98	0	4,008.37	0	3,861.84	0	3,702.66	0	3,393.77	0	3,045.68	0	2,697.59	0	2,349.51	0	2,001.49	0	1,653.43	0	1,306.04	0	957.98	0	611.84	0	269.90	0	

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
 NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
 NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
 NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 05/25/2016 BY: JM
 DATE COMPUTED: 05/26/2016 BY: CL
 DATE ISSUED: 05/26/2016

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
 OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

