



BARGE: GM 1020

ULLAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 PORT	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-1/2	- 01-1/2	02-0/8	- 02-0/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8
3 STBD	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-1/2	- 01-1/2	02-1/8	- 02-1/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS - 01-0/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11"

LENGTH BETWEEN DRAFT MARKS: 262'-00"

May 6, 2017

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR GAUGING WITH HERMETIC GAUGE

REFERENCE GAUGE HEIGHT: 15'-10 7/8"

Table with 26 columns representing gauge heights from 1 FT. to 16 FT. and rows representing depth measurements from 0 to 11 feet. Each cell contains capacity values for three different gauging methods.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP OF HERMETIC VALVE, ON 18" DECK PIPE, USING THE HERMETIC DEVICE.

NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 04/29/2017 BY: JM
DATE COMPUTED: 05/06/2017 BY: CL
DATE ISSUED: 05/06/2017

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR GAUGING WITH HERMETIC GAUGE

REFERENCE GAUGE HEIGHT: 15'-11 1/8"

Table with columns for IN (0-16) and FT. (1-16) showing capacity values in barrels. Each cell contains a numerical value representing capacity.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP OF HERMETIC VALVE, ON 18" DECK PIPE, USING THE HERMETIC DEVICE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 04/29/2017 BY: JM
DATE COMPUTED: 05/06/2017 BY: CL
DATE ISSUED: 05/06/2017

