

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL INNAGE GAUGING AT 8" GAUGE HATCH

HULL No. 08-2372

Table with 25 columns (0 FT. to 15 FT.) and 25 rows (0 to 11). Each cell contains a numerical value representing capacity in barrels, with fractional increments (1/4, 1/2, 3/4) indicating measurement levels.

NOTE: GAUGE POINT: TOP LIP OF 8" GAUGE HATCH OPPOSITE HINGE. NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. REFERENCE GAUGE HEIGHT: 13' 3" OPPOSITE HINGE OF 8" HATCH

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF. DATE COMPUTED: 5-31-09 BY:WHF. DATE ISSUED: 6-8-09



BARGE "FMT 5032" FLORIDA MARINE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL INNAGE GAUGING AT 8" GAUGE HATCH

HULL No. 08-2372

Table with columns for depth (0 FT. to 15 FT.) and corresponding capacity values. The table is organized into rows for each depth and columns for each measurement point.

NOTE: GAUGE POINT: TOP LIP OF 8" GAUGE HATCH OPPOSITE HINGE... NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK... REFERENCE GAUGE HEIGHT: 12' 11 3/4" OPPOSITE HINGE OF 8" HATCH

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF... DATE COMPUTED: 5-31-09 BY:WHF... DATE ISSUED: 6-8-09



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL ULLAGE GAUGING AT 8" GAUGE HATCH

HULL No. 08-2372

Table with columns for height (IN, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT.) and rows for capacity (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11).

NOTE: GAUGE POINT: TOP LIP OF 8" GAUGE HATCH OPPOSITE HINGE
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. TRIM CORRECTION NOT REQUIRED
REFERENCE GAUGE HEIGHT: 13' 2 1/4" OPPOSITE HINGE OF 8" HATCH

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF
DATE COMPUTED: 5-31-09 BY:WHF
DATE ISSUED: 6-8-09

INTERTEK - CALEB BRETT

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR CLOSED ULLAGE GAUGING AT HERMETIC VALVE

HULL No. 08-2372

Table with columns for depth (0 to 15 FT) and ullage measurements (IN) for various gauge points (0 to 15 FT). Each cell contains a numerical value representing capacity in barrels.

NOTE: GAUGE POINT: HERMETIC STANDPIPE
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. TRIM CORRECTION NOT REQUIRED
REFERENCE GAUGE HEIGHT: 15'-3 1/4" REFERENCE MARK ON HERMETIC GAUGE TAPE

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF
DATE COMPUTED: 5-31-09 BY:WHF
DATE ISSUED: 6-8-09

INTERTEK - CALEB BRETT

Handwritten signature

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR CLOSED ULLAGE GAUGING AT HERMETIC VALVE

HULL No. 08-2372

Main data table with columns for height (0 to 15 FT) and various gauge points (0, 1/4, 1/2, 3/4) for each height, listing capacity values in barrels.

NOTE: GAUGE POINT: HERMETIC STANDPIPE

NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. TRIM CORRECTION NOT REQUIRED

REFERENCE GAUGE HEIGHT: 15'-3 3/4"

REFERENCE MARK ON HERMETIC GAUGE TAPE

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF

DATE COMPUTED: 5-31-09 BY:WHF

DATE ISSUED: 6-8-09

INTERTEK - CALEB BRETT

Signature of Caleb Brett

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR CLOSED ULLAGE GAUGING AT HERMETIC VALVE

HULL No. 08-2372

Table with columns for height (IN, FT.) and capacity (0-15 FT.). Rows are grouped by height (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 FT.). Each row contains 28 data points representing capacity in barrels at different gauge heights.

NOTE: GAUGE POINT: HERMETIC STANDPIPE... THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY... DATE STRAPPED: 5-15-2009 BY:JMF...



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR CLOSED ULLAGE GAUGING AT HERMETIC VALVE

HULL No. 08-2372

Table with 26 columns (IN 0 FT. to IN 15 FT.) and 26 rows (0 to 11). Each row contains capacity values for different gauge heights (1/4, 1/2, 3/4) at each height.

NOTE: GAUGE POINT: HERMETIC STANDPIPE
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. TRIM CORRECTION NOT REQUIRED
REFERENCE GAUGE HEIGHT: 15'-1 1/2" REFERENCE MARK ON HERMETIC GAUGE TAPE

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 5-15-2009 BY:JMF
DATE COMPUTED: 5-31-09 BY:WHF
DATE ISSUED: 6-8-09

INTERTEK - CALEB BRETT



GAUGE HEIGHT - PORT: 3' 11"
 GAUGE HEIGHT - STBD: 3' 10 3/4"

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

IN	0 FT.	IN	0 FT.	IN	1 FT.	IN	1 FT.	IN	2 FT.	IN	2 FT.	IN	3 FT.	IN	3 FT.	IN	4 FT.	IN	4 FT.
0	0	6	1,080	0	2,160	6	3,240	0	4,320	6	5,400	0	6,480	6	7,493	0		6	
1/8	23	1/8	1,103	1/8	2,183	1/8	3,263	1/8	4,343	1/8	5,423	1/8	6,503	1/8	7,498	1/8		1/8	
1/4	45	1/4	1,125	1/4	2,205	1/4	3,285	1/4	4,365	1/4	5,445	1/4	6,525	1/4	7,502	1/4		1/4	
3/8	68	3/8	1,148	3/8	2,228	3/8	3,308	3/8	4,388	3/8	5,468	3/8	6,548	3/8	7,504	3/8		3/8	
1/2	90	1/2	1,170	1/2	2,250	1/2	3,330	1/2	4,410	1/2	5,490	1/2	6,570	1/2	7,505	1/2		1/2	
5/8	113	5/8	1,193	5/8	2,273	5/8	3,353	5/8	4,433	5/8	5,513	5/8	6,593	5/8	7,506	5/8		5/8	
3/4	135	3/4	1,215	3/4	2,295	3/4	3,375	3/4	4,455	3/4	5,535	3/4	6,615	3/4		3/4		3/4	
7/8	158	7/8	1,238	7/8	2,318	7/8	3,398	7/8	4,478	7/8	5,558	7/8	6,638	7/8		7/8		7/8	
1	180	7	1,260	1	2,340	7	3,420	1	4,500	7	5,580	1	6,660	7		1		7	
1/8	203	1/8	1,283	1/8	2,363	1/8	3,443	1/8	4,523	1/8	5,603	1/8	6,683	1/8		1/8		1/8	
1/4	225	1/4	1,305	1/4	2,385	1/4	3,465	1/4	4,545	1/4	5,625	1/4	6,705	1/4		1/4		1/4	
3/8	248	3/8	1,328	3/8	2,408	3/8	3,488	3/8	4,568	3/8	5,648	3/8	6,728	3/8		3/8		3/8	
1/2	270	1/2	1,350	1/2	2,430	1/2	3,510	1/2	4,590	1/2	5,670	1/2	6,750	1/2		1/2		1/2	
5/8	293	5/8	1,373	5/8	2,453	5/8	3,533	5/8	4,613	5/8	5,693	5/8	6,773	5/8		5/8		5/8	
3/4	315	3/4	1,395	3/4	2,475	3/4	3,555	3/4	4,635	3/4	5,715	3/4	6,795	3/4		3/4		3/4	
7/8	338	7/8	1,418	7/8	2,498	7/8	3,578	7/8	4,658	7/8	5,738	7/8	6,818	7/8		7/8		7/8	
2	360	8	1,440	2	2,520	8	3,600	2	4,680	8	5,760	2	6,840	8		2		8	
1/8	383	1/8	1,463	1/8	2,543	1/8	3,623	1/8	4,703	1/8	5,783	1/8	6,863	1/8		1/8		1/8	
1/4	405	1/4	1,485	1/4	2,565	1/4	3,645	1/4	4,725	1/4	5,805	1/4	6,885	1/4		1/4		1/4	
3/8	428	3/8	1,508	3/8	2,588	3/8	3,668	3/8	4,748	3/8	5,828	3/8	6,908	3/8		3/8		3/8	
1/2	450	1/2	1,530	1/2	2,610	1/2	3,690	1/2	4,770	1/2	5,850	1/2	6,930	1/2		1/2		1/2	
5/8	473	5/8	1,553	5/8	2,633	5/8	3,713	5/8	4,793	5/8	5,873	5/8	6,953	5/8		5/8		5/8	
3/4	495	3/4	1,575	3/4	2,655	3/4	3,735	3/4	4,815	3/4	5,895	3/4	6,975	3/4		3/4		3/4	
7/8	518	7/8	1,598	7/8	2,678	7/8	3,758	7/8	4,838	7/8	5,918	7/8	6,998	7/8		7/8		7/8	
3	540	9	1,620	3	2,700	9	3,780	3	4,860	9	5,940	3	7,020	9		3		9	
1/8	563	1/8	1,643	1/8	2,723	1/8	3,803	1/8	4,883	1/8	5,963	1/8	7,043	1/8		1/8		1/8	
1/4	585	1/4	1,665	1/4	2,745	1/4	3,825	1/4	4,905	1/4	5,985	1/4	7,065	1/4		1/4		1/4	
3/8	608	3/8	1,688	3/8	2,768	3/8	3,848	3/8	4,928	3/8	6,008	3/8	7,088	3/8		3/8		3/8	
1/2	630	1/2	1,710	1/2	2,790	1/2	3,870	1/2	4,950	1/2	6,030	1/2	7,110	1/2		1/2		1/2	
5/8	653	5/8	1,733	5/8	2,813	5/8	3,893	5/8	4,973	5/8	6,053	5/8	7,133	5/8		5/8		5/8	
3/4	675	3/4	1,755	3/4	2,835	3/4	3,915	3/4	4,995	3/4	6,075	3/4	7,155	3/4		3/4		3/4	
7/8	698	7/8	1,778	7/8	2,858	7/8	3,938	7/8	5,018	7/8	6,098	7/8	7,178	7/8		7/8		7/8	
4	720	10	1,800	4	2,880	10	3,960	4	5,040	10	6,120	4	7,200	10		4		10	
1/8	743	1/8	1,823	1/8	2,903	1/8	3,983	1/8	5,063	1/8	6,143	1/8	7,223	1/8		1/8		1/8	
1/4	765	1/4	1,845	1/4	2,925	1/4	4,005	1/4	5,085	1/4	6,165	1/4	7,245	1/4		1/4		1/4	
3/8	788	3/8	1,868	3/8	2,948	3/8	4,028	3/8	5,108	3/8	6,188	3/8	7,268	3/8		3/8		3/8	
1/2	810	1/2	1,890	1/2	2,970	1/2	4,050	1/2	5,130	1/2	6,210	1/2	7,290	1/2		1/2		1/2	
5/8	833	5/8	1,913	5/8	2,993	5/8	4,073	5/8	5,153	5/8	6,233	5/8	7,313	5/8		5/8		5/8	
3/4	855	3/4	1,935	3/4	3,015	3/4	4,095	3/4	5,175	3/4	6,255	3/4	7,335	3/4		3/4		3/4	
7/8	878	7/8	1,958	7/8	3,038	7/8	4,118	7/8	5,198	7/8	6,278	7/8	7,358	7/8		7/8		7/8	
5	900	11	1,980	5	3,060	11	4,140	5	5,220	11	6,300	5	7,380	11		5		11	
1/8	923	1/8	2,003	1/8	3,083	1/8	4,163	1/8	5,243	1/8	6,323	1/8	7,401	1/8		1/8		1/8	
1/4	945	1/4	2,025	1/4	3,105	1/4	4,185	1/4	5,265	1/4	6,345	1/4	7,420	1/4		1/4		1/4	
3/8	968	3/8	2,048	3/8	3,128	3/8	4,208	3/8	5,288	3/8	6,368	3/8	7,437	3/8		3/8		3/8	
1/2	990	1/2	2,070	1/2	3,150	1/2	4,230	1/2	5,310	1/2	6,390	1/2	7,452	1/2		1/2		1/2	
5/8	1,013	5/8	2,093	5/8	3,173	5/8	4,253	5/8	5,333	5/8	6,413	5/8	7,465	5/8		5/8		5/8	
3/4	1,035	3/4	2,115	3/4	3,195	3/4	4,275	3/4	5,355	3/4	6,435	3/4	7,476	3/4		3/4		3/4	
7/8	1,058	7/8	2,138	7/8	3,218	7/8	4,298	7/8	5,378	7/8	6,458	7/8	7,485	7/8		7/8		7/8	

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

INTERTEK - CALEB BRETT

DATE STRAPPED: 5-15-2009 BY:JMF
 DATE COMPUTED: 5-31-09 BY:WHF
 DATE ISSUED: 6-8-09

